

Lift&Drive

70E/ES and 90E/ES



Lift&Drive 70E/ES and 90E/ES

The Lift&Drive 70 and 90E/ES are our neat and maneuverable lifting trolleys, designed with a special focus on ergonomics. The chassis of the trolleys is merely 435 mm wide, making them very light and flexible. We offer a standard version of the trolley, but we have also developed ones that are specifically developed to be used in environments such as larger catering establishments, archives, and pharmacies, where they go by the name "crate lifter".

There are a large number of standard tools to choose from. The masts are equipped with screw drives and are available in different heights. Despite their slight weight the trolleys can handle weights up to either 70 or 90 kg. To ensure maximal safety the trolleys possess a built-in release function, which serves as protection from crushing injuries and prevents the trolley from tipping over.

Technical Specifikations for the 70E/ES and 90E/ES

Mast	Overall height, standard	Overall height, low-built	Total lifting height, standard	Total lifting height, low-built	Length of stroke
-250	1442	1413	1123	1094	964
standard	1692	1663	1373	1344	1214
+250	1942	1913	1623	1594	1464
+500	2192	2163	1873	1844	1714

Minimum lifting height, standard, low-built

Total width

Length (without loading platform) standard, low-built

Loading platform (L x W)

Wheel diameter (front/rear) standard, low-built

Max load 70E, 70ES Max load 90E, 90ES Dead weight Battery voltage

Battery capacity
Charging voltage

Material, Lift&Drive 70E, 90E Material, Lift&Drive 70ES, 90ES 139, 110 mm 498 mm

735, 716 mm 440x498 mm

80/100, 50/75 mm

70 kg 90 kg 33 kg 24 V 6.5 Ah

230VAC/50Hz or 115VAC/60Hz Chassis in powder-coated steel Chassis in stainless steel

Platform can if necessary be moved up 110 mm in the sledge.

For further info please contact your sales representative

PRONOMIC AB info@pronomic.se www.pronomic.se

One of our main strengths is that we're in charge of both design and production.

